

## DISPLAY DEVICE

## BACKGROUND OF THE INVENTION

## Field of the Invention

5           This invention relates to a display device. More particularly, it relates to a display device adapted to highly efficiently take out light emitted from electroluminescent (EL) elements that operate as so many display pixels to the outside.

## 10   Related Background Art

          Display devices comprising a plurality of EL elements arranged two-dimensionally on a same substrate are known. However, in any known display devices, the ratio of the quantity of light that can be externally  
15   taken out to the total quantity of light emitted from each of the EL elements is not very large.

          FIG. 1 of the accompanying drawings is a schematic cross sectional view of an EL element of a known display device, illustrating its basic structure.

20   Referring to FIG. 1, the EL element 600 is formed by sequentially laying a transparent electrode 520, an electroluminescent (EL) layer 510 and a reflector electrode 500 on a transparent substrate 550 in the above mentioned order. Light emitted from the EL layer  
25   510 is totally reflected at the interface B1 of the transparent substrate 550 and the transparent electrode 520 and the interface B2 of the transparent substrate

550 and ambient air. If the refractive index of the transparent electrode 520 is 1.8 and that of the transparent substrate 550 is 1.5, the quantity of light confined within the EL element 600 due to total reflection at the interface B1 is about 51% of the total quantity of light emitted from the EL element 600. On the other hand, the quantity of light confined within the EL element 600 due to total reflection at the interface B2 is about 32% of the total quantity of light emitted from the EL element 600. Therefore, the quantity of light that can be externally taken out from the transparent substrate 550 is only about 17% of the total quantity of emitted light.

Meanwhile, Optics Letters, March 15 (1997) pp. 396 to 398, discloses an EL element realized by adding a transparent member having a trapezoidal cross section to the above described basic structure, from which light can be taken out at an improved efficiency. FIG. 2 of the accompanying drawings is a schematic cross sectional view of such an EL element. In FIG. 2, the components that are same as those of FIG. 1 are denoted respectively by the same reference symbols.

Referring to FIG. 2, the EL element 600 has a sandwich structure where an EL layer 510 is sandwiched between a reflector electrode 500 and a transparent electrode 520. The EL element 600 is laid on a transparent member 540 having a trapezoidal cross

section and formed on a transparent substrate 550.

When such EL elements are applied to a two-dimensional display device, the transparent member 540 of each EL element is typically realized in the form of a frustum of quadrangular pyramid. Then, a reflection film 530 is formed on the slopes of the transparent member 540.

With an EL element 600 having a configuration as shown in FIG. 2, no total reflection takes place at the interface 1 when the refractive index of the transparent member 540 is made greater than that of the transparent electrode. On the other hand, if total reflection occurs at the interface 2 of the transparent substrate 550 and ambient air, light  $I_2$  totally reflected by the interface 2 is reflected again by the reflection film 530 and taken out of the transparent substrate 550 into ambient air. Similarly, if total reflection occurs at the interface 3 of the transparent member 540 and the transparent substrate 550, light  $I_3$  totally reflected by the interface 3 is reflected again by the reflection film 530 and taken out of the transparent member 540. It may be needless to note that light emitted from the EL layer 510, transmitted through the transparent electrode 520 and directly reflected by the reflection film 530 goes out of the transparent substrate 550 into ambient air. Therefore, the above described arrangement allows light emitted from the EL layer 510 to be highly efficiently taken

out to the outside.

However, if the reflection film 530 formed on the slopes of the transparent member 540 is made of metal in the above described EL element, it needs to be  
5 formed so as not to contact the transparent electrode 520 and the reflector electrode 500. It is not easy to form such a reflection film. Additionally, although not shown in FIG. 2, the sandwich structure sandwiching the EL layer 510 needs to be covered by a protection  
10 film in order to prolong the service life of the EL element 600. Then, such a protection film has to be prepared independently from the process of manufacturing the transparent member 540 to increase the number of total manufacturing steps and baffle  
15 effects for reducing the manufacturing cost.

#### SUMMARY OF THE INVENTION

In view of the above identified circumstances, it is therefore the object of the present invention to  
20 provide a display device that is free from the problems of the conventional technology and adapted to highly efficiently take out light emitted from the EL layers thereof to the outside, while it can be manufactured at low cost.

25 According to the invention, the above object is achieved by providing a display device comprising:

a transparent substrate;

a plurality of electroluminescent elements arranged on the transparent substrate, each of the electroluminescent elements being formed by sequentially laying a transparent electrode, an  
5 electroluminescent layer and a reflector electrode on the transparent substrate;

transparent members having a profile of a frustum of pyramid or cone and respectively covering the electroluminescent elements; and  
10 reflection films formed respectively on the surfaces of the transparent members.

In another aspect of the invention, there is also provided a display device comprising:

a transparent substrate;  
15 a plurality of electroluminescent elements arranged on the transparent substrate, each of the electroluminescent elements being formed by sequentially laying a transparent electrode, an electroluminescent layer and a reflector electrode on  
20 the transparent substrate;

transparent members respectively covering the electroluminescent elements, each of the transparent members partly having a curved surface showing a positive curvature, a part thereof held in contact with  
25 the transparent substrate having a curved surface showing a negative curvature; and

reflection films formed respectively on the

surfaces of the transparent members.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic cross sectional view of a  
5 known EL element.

FIG. 2 is a schematic cross sectional view of  
another known EL element.

FIG. 3 is a schematic cross sectional view of an  
electroluminescent element operating as a pixel in the  
10 first embodiment of display device according to the  
invention.

FIGS. 4A, 4B, 4C and 4D are partial schematic  
cross sectional views of the embodiment of display  
device of FIG. 3, illustrating different manufacturing  
15 steps.

FIG. 5 is a schematic cross sectional view of an  
electroluminescent element operating as a pixel in the  
second embodiment of display device according to the  
invention.

FIGS. 6A and 6B are a partial schematic plan view  
20 and a corresponding partial schematic cross sectional  
view of the third embodiment of display device  
according to the invention.

FIG. 7 is a schematic cross sectional view of an  
25 electroluminescent element operating as a pixel in the  
fourth embodiment of display device according to the  
invention.

FIG. 8 is a schematic cross sectional view of an electroluminescent element operating as a pixel in the fifth embodiment of display device according to the invention.

5        FIG. 9 is a schematic cross sectional view of an electroluminescent element operating as a pixel in the sixth embodiment of display device according to the invention.

10       FIG. 10 is a partial cross sectional view of a silica aerogel film formed on a transparent substrate.

FIG. 11 is a schematic cross sectional view of an electroluminescent element formed on a transparent substrate carrying a silica aerogel film formed thereon.

15       FIG. 12 is a schematic cross sectional view of an electroluminescent element having a silica aerogel film formed on a transparent substrate and operating as a pixel in the seventh embodiment of display device according to the invention.

20       FIG. 13 is a schematic cross sectional view of an electroluminescent element having a low refractive index light transmitting film formed on a transparent substrate and operating as a pixel in the eighth embodiment of display device according to the invention.

25

FIG. 14 is schematic cross sectional view similar to FIG. 13 but illustrating the behavior of rays of

light in the electroluminescent element.

FIG. 15 is a schematic cross sectional view of an electroluminescent element having a half mirror formed on a transparent substrate and operating as a pixel in the ninth embodiment of display device according to the invention.

FIG. 16 is a schematic cross sectional view of an electroluminescent element having a half mirror formed on a transparent substrate and operating as a pixel in the tenth embodiment of display device according to the invention.

FIG. 17 is a conceptual illustration of a projector realized by using a display device shown in FIG. 15 or FIG. 16.

FIG. 18 is a schematic cross sectional view of a half mirror structure having eight layers.

FIG. 19 is a graph illustrating the reflectance of the half mirror structure of FIG. 18.

FIGS. 20A, 20B and 20C are graphs illustrating the reflectance of a half mirror structure having eight layers in different aspects.

FIG. 21 is a schematic cross sectional view of an electroluminescent element having a light absorbing layer formed on a transparent substrate and operating as a pixel in the eleventh embodiment of display device according to the invention.

FIG. 22 is a schematic cross sectional view of an



electroluminescent element having a light absorbing layer formed on a transparent substrate and operating as a pixel in the twelfth embodiment of display device according to the invention.

5

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now, the present invention will be described by referring to the accompanying drawings that illustrate preferred embodiments of the invention.

10

FIG. 3 is a schematic cross sectional view of an electroluminescent (EL) element operating as a pixel in the first embodiment of display device according to the invention. Referring to FIG. 3, the EL element 300 is formed by sequentially laying a transparent electrode 120, an electroluminescent (EL) layer 110 and a reflector electrode 100 on a transparent substrate 150 in the above mentioned order. Additionally, a transparent member 140 having a trapezoidal cross section is formed on the transparent substrate 150 to cover the EL element 300. In other words, the EL element 300 is protected from ambient air by the transparent member 140. A reflection film 130 is formed as coat on the entire surface of the transparent member 140.

25

The EL layer 110 of the EL element shown in FIG. 3 emits light as a voltage is applied between the reflector electrode 100 and the transparent electrode

120. Light emitted from the EL layer 110 is mostly transmitted through the transparent electrode 120 and the transparent substrate 150 and externally taken out.

On the other hand, a part of light emitted from the EL layer 110 is totally reflected by the interface B1 of the transparent electrode 120 and the transparent substrate 150. The totally reflected light is reflected by the reflection film 130 and transmitted through the transparent substrate 150 before it is externally taken out. While the totally reflected light is refracted twice by the interface B1 and the interface B2, it is shown in FIG. 3 as if it proceeds straight for the purpose of simplicity.

Another part of light emitted from the EL layer 110 is refracted by the interface B1 and totally reflected by the interface B2 of the transparent substrate 150 and ambient air. However, the totally reflected light is also reflected by the reflection film 130 and transmitted through the transparent substrate 150 before it is externally taken out. In this way, light emitted from the EL element 300 is highly efficiently taken out to the outside.

While a single EL element is shown in FIG. 3, a plurality of identical EL elements are arranged two-dimensionally in the embodiment of display device. When the EL elements are arranged two-dimensionally, the transparent members are typically realized in the

form of a frustum of quadrangular pyramid.

Now, the process of manufacturing EL elements will be described by referring to FIGS. 4A through 4D.

FIGS. 4A through 4D are partial schematic cross sectional views of the embodiment of display device of FIG. 3, illustrating some of the EL elements in different manufacturing steps.

Firstly, as shown in FIG. 4A, a transparent electrode 120 typically made of ITO, an EL layer 110 made of an organic or inorganic material and a reflector electrode 100 made of metal film are sequentially formed on a transparent substrate 150 typically made of glass or plastic in the above mentioned order.

Then, the electrodes and the EL layer are removed by pattern etching except the necessary areas to produce EL elements 300 arranged in a manner as shown in FIG. 4B. Then, a transparent layer 140a is formed to cover the EL elements 300. The transparent layer 140a is typically made of titanium oxide.

Subsequently, the transparent layer 140a is partly removed by pattern etching to produce a plurality of transparent members 140, each having slopes 145 as shown in FIG. 4C, to completely cover the respective EL elements 300.

Finally, as shown in FIG. 4D, a reflection film 130 of metal or dielectric is formed on the entire

surface of the transparent substrate 150 by deposition. In this way, a display device comprising a plurality of EL elements 300 formed on a transparent substrate is manufactured.

5           FIG. 5 is a schematic cross sectional view of an electroluminescent (EL) element operating as a pixel in the second embodiment of display device according to the invention. This embodiment differs from the first embodiment only in that the reflection film 130 is  
10       formed only on the slopes of the transparent members 140. In other words, no reflection film is formed on the top surface 141 of the transparent members 140. Otherwise, the second embodiment is same and identical with the first embodiment. Therefore, in FIG. 5, the  
15       components that are same as or similar to those of FIG. 3 are denoted respectively by the same reference symbols and will not be described any further.

          Referring to FIG. 5, in this embodiment again, a part of light emitted from the EL layer 110 is totally  
20       reflected by the interface B1 of the transparent electrode 120 and the transparent substrate 150. The totally reflected light is then reflected by the reflection film 130 and transmitted through the transparent substrate 150 before it is taken out into  
25       ambient air. While the light totally reflected by the reflection film 130 is refracted twice by the interface B1 and the interface B2, it is shown in FIG. 5 as if it

proceeds straight for the purpose of simplicity. Since no reflection film is formed on the top surface 141 of the transparent member 140, this embodiment provides an advantage that heat emitted with light can be easily  
5 dissipated if compared with the first embodiment.

The second embodiment of display device is produced by removing the reflection film that has been formed on the entire surface of the transparent members 140 as shown in FIG. 4D from the top surfaces 141  
10 thereof by photo-etching after the manufacturing steps shown in FIGS. 4A through 4D and described above by referring to the first embodiment.

FIGS. 6A and 6B are a partial schematic plan view and a corresponding partial schematic cross sectional  
15 view of the third embodiment of display device according to the invention. FIG. 6A is a partial schematic plan view and FIG. 6B is a schematic cross sectional view taken along line 6B-6B in FIG. 6A. In FIGS. 6A and 6B, the components that are same as or  
20 similar to those of FIGS. 3 through 5 are denoted respectively by the same reference symbols and will not be described any further.

In this embodiment, each EL element 300 and a corresponding drive element 400 such as TFT for driving  
25 the EL element 300 are covered by a transparent member 140. Note that the wires between each element 300 and the corresponding drive element 400, which may be a

TFT, are not shown in FIGS. 6A and 6B for the purpose of simplicity. Each transparent member 140 is realized in the form of a frustum of quadrangular prism having a top surface 141. Therefore, each transparent member 140 shows a trapezoidal cross section. Although not shown in FIG. 6B, the surfaces of the transparent members 140 are covered by a reflection film as shown in FIG. 3 or FIG. 5.

In this embodiment, the gaps separating the plurality of transparent members 140 that are covered by a reflection film are filled with an insulating body 800 and row-directional wires 900 and column-directional wires 700 are formed on the insulating body 800. The drive element 400 connected to each EL element 300 is by turn connected to a column-directional wire 700 by way of an outgoing wire 701. The outgoing wire 701 and the column-directional wire 700 are connected by way of a through hole 702 through the insulating body 800. Similarly, the drive element 400 connected to each element 300 is also connected to a row-directional wire 900 by way of an outgoing wire 901. With the above described arrangement, the EL elements 300 of this embodiment of display device emit light as so many pixels of a two-dimensional display screen.

While each EL element 300 of FIGS. 6A and 6B is connected to a column-directional wire 700 and a row-

directional wire 900 by way of a corresponding drive element 400, alternatively it may be directly connected to the wires without a drive element 400 interposed between them. While the transparent members have a profile of a frustum of quadrangular pyramid in the above description, they may alternatively have a profile of a frustum of cone. Still alternatively, the transparent members may have a profile of a part of a ball.

FIG. 7 is a schematic cross sectional view of an electroluminescent (EL) element operating as a pixel in the fourth embodiment of display device according to the invention. In FIG. 7, the components that are same as or similar to those of FIG. 3 are denoted respectively by the same reference symbols and will not be described any further.

In this embodiment, the transparent members 340 are so formed as to show a profile of a part of a ball. More specifically, each transparent member 340 has a top section that shows a profile of a part of a ball with a positive curvature and a bottom section, or an outskirt section, that is connected to the transparent substrate 150 and shows a profile of a curved slope with a negative curvature. In other words, the transparent member 340 has a convex top section and a concave outskirt section. Then, the surface of each transparent member 340 is covered by a reflection film

330. The reflection film 330 operates as a concave mirror for the EL element 300.

Each transparent member 340 may be formed by causing a drop of hot and molten plastic to fall onto the corresponding EL element 300 and subsequently solidifying the molten plastic. The inclination of the outskirt section is determined as a function of the contact angle of the transparent substrate 150 and the liquefied transparent member 340. The inclination of the outskirt section may be controlled by pressing the semispherical transparent member 340 from the top before the latter is solidified.

In the EL element shown in FIG. 7, the EL layer 110 emits light when a voltage is applied between the reflector electrode 100 and the transparent electrode 120. Light emitted from the EL layer 110 is transmitted through the transparent electrode 120 and the transparent substrate 150 before it is externally taken out.

On the other hand, a part of light emitted from the EL layer 110 is totally reflected by the interface B1 of the transparent electrode 120 and the transparent substrate 150. The totally reflected light is reflected by the reflection film 330 and transmitted through the transparent substrate 150 before it is taken out into ambient air. While the totally reflected light is refracted twice by the interface B1



and the interface B2, it is shown in FIG. 7 as if it proceeds straight for the purpose of simplicity.

Another part of light emitted from the EL layer 110 is refracted by the interface B1 and totally reflected by the interface B2 of the transparent substrate 150 and ambient air. However, the totally reflected light is also reflected by the reflection film 330 and transmitted through the transparent substrate 150 before it is taken out into ambient air.

Almost no light gets to the top section S of the transparent member 340. Rays of light proceeding substantially perpendicularly relative to the end facets of the EL element 300 are not totally reflected by the interface B1 but transmitted through the transparent substrate 150 and taken out into ambient air. Thus, if the top section S is not accurately semispherical but distorted somewhat, it does not significantly affect the function of the EL element 300. In this way, light emitted from the EL element 300 is highly efficiently taken out to the outside.

FIG. 8 is a schematic cross sectional view of an electroluminescent (EL) element operating as a pixel in the fifth embodiment of display device according to the invention. This embodiment differs from the above described fourth embodiment only in that the focal plane of the concave mirror formed by the reflection film 330 is located inside the element EL element 300.

Otherwise, this embodiment is identical with the fourth embodiment. Therefore, in FIG. 8, the components that are same as or similar to those of FIG. 7 are denoted respectively by the same reference symbols and will not  
5 be described any further.

In this embodiment, rays of light emitted from the end facets of the EL layer 110 are reflected by the concave mirror section of the transparent member 340 to form a flux of parallel rays of light, which is then  
10 taken out to the outside through the transparent substrate 150. In the outskirts section of the transparent member 340, all the light reflected by the interfaces B1, B2 is reflected again before it is externally taken out into ambient air. Thus, light is  
15 externally taken out to a large proportion.

In this embodiment again, almost no light gets to the top section S of the transparent member 340. Rays of light proceeding substantially perpendicularly relative to the end facets of the EL element 300 are  
20 not totally reflected by the interface B1 but transmitted through the transparent substrate 150 and taken out into ambient air. Thus, if the top section S is not accurately semispherical but distorted somewhat, it does not significantly affect the function of the EL  
25 element 300.

While the outskirts section of the transparent member 340 is realized in the form of a curved surface

with a negative curvature (concave surface) in either of the embodiments shown in FIGS. 7 and 8, an effect similar to that of FIG. 7 or 8 can be obtained when the transparent member 340 is made to show a profile having  
5 no such a concave surface, or a profile of a part of a ball such as a semispherical profile having only a positive curvature.

FIG. 9 is a schematic cross sectional view of an electroluminescent (EL) element operating as a pixel in  
10 the sixth embodiment of display device according to the invention. In FIG. 9, the components that are same as or similar to those of FIG. 7 are denoted respectively by the same reference symbols and will not be described any further.

15 In this embodiment, the transparent substrate 150 is provided with grooves 152, each having a size sufficiently covering an EL element 300. A thin transparent plate 151 typically made of titanium oxide ( $\text{TiO}_2$ ) is formed on the groove 152. An EL element 300  
20 is formed on the transparent plate 151. In other words, the inside of the groove 152 is a void and an air gap is formed between the transparent plate 151 and the substrate 150.

In this embodiment, light from the EL element 300  
25 that is transmitted through transparent plate 151 and the groove 152 containing a void therein and strikes the substrate 150 is not totally reflected by the

substrate 150. In other words, totally reflected light in the transparent substrate 150 will not be propagated into other pixels nor confined within the substrate 150. Therefore, light emitted from the EL element 300 is effectively taken out into ambient air by the reflector hemisphere formed by the transparent member 340 and the reflection film 330.

While the transparent member 340 has a profile of a part of a ball in FIG. 9, it may be replaced by a transparent member 140 having a profile of a frustum of quadrangular pyramid as shown in FIG. 3 or that of a frustum of cone.

Meanwhile, it may be conceivable to form a low refractive index film such as a silica aerogel film on the transparent substrate of a display device according to the invention in order to improve the efficiency of taking out light from the transparent substrate. Such arrangements will be discussed below.

FIG. 10 is a partial cross sectional view of a silica aerogel film 210 formed on a transparent substrate 211. Such a silica aerogel film 210 typically shows a refractive index of 1.03. Light 212 striking the silica aerogel film 210 from air is refracted by the interface of the silica aerogel film 210 and the transparent substrate 211 according to the Snell's law of refraction to become light 214. Light 214 is then emitted into air from the lower surface 234

of the transparent substrate 211 as light 215. Since the transparent substrate 211 is sandwiched between substances having respective refractive indexes that are lower than the refractive index of itself, no total reflection takes place in the transparent substrate 211. However, light 213 is reflected in the direction of regular reflection as a result of Fresnel reflection at the interface 233 to give rise to light 216. The intensity of light 216 increases as the angle of incidence of light 213 is reduced to become quasi-parallel relative to the transparent substrate 211.

FIG. 11 is a schematic cross sectional view of an electroluminescent (EL) element 235 formed on a transparent substrate 211 carrying a silica aerogel film 210 formed thereon. In FIG. 11, the components that are same as or similar to those of FIG. 10 are denoted respectively by the same reference symbols and will not be described any further.

Referring to FIG. 11, the EL element 235 is formed by sequentially laying a transparent electrode 217 typically made of ITO, an EL layer 218 made of an organic or inorganic material and a reflector electrode 219 made of metal are sequentially formed on a silica aerogel film 210 in the above mentioned order. Light 221 emitted from point 220 of the EL layer 218 is transmitted through the transparent electrode 217 and the silica aerogel film 210 to get to the interface 233

of the silica aerogel film 210 and the transparent substrate 211. Then, light 225 produced as a result of Fresnel reflection at the interface 233 is then propagated in the silica aerogel film 210 in the direction of regular reflection. The propagated light then goes into adjacent EL elements (not shown) and is randomly reflected by them before proceeding in the direction of observation. Thus, the propagated light that goes into adjacent EL elements can give rise to undesired noise in the latter. Additionally, the propagated light 225 constitutes a loss of light for the EL element from which it originates to consequently reduce the efficiency of effectively utilizing light.

FIG. 12 is a schematic cross sectional view of an electroluminescent element having a silica aerogel film formed on a transparent substrate and operating as a pixel in the seventh embodiment of display device according to the invention. In FIG. 12, the components that are same as or similar to those of FIGS. 7 and 11 are denoted respectively by the same reference symbols and will not be described any further.

In this embodiment, the silica aerogel film 210 has a size substantially same as that of the EL element 235. Light 227 emitted from point 226 of the EL layer 218 undergoes Fresnel reflection at the interface 234 of the silica aerogel film 210 and the transparent substrate 211 to become light 229, which is then

reflected by the reflection film 330 formed on the surface of transparent member 340 to become light 230 that goes into air. Therefore, light that undergoes Fresnel reflection does not go into adjacent EL elements (not shown) nor totally reflected in the transparent substrate 211 to consequently raise the efficiency of utilization of light of this embodiment.

FIG. 13 is a schematic cross sectional view of an electroluminescent (EL) element having a low refractive index light transmitting film formed on a transparent substrate and operating as a pixel in the eighth embodiment of display device according to the invention.

Referring to FIG. 13, an insulating member is buried between any two adjacent electroluminescent (EL) elements in this embodiment. In FIG. 13, there are shown an EL layer 241, a transparent electrode 242 typically made of ITO, a reflector electrode 243 typically made of metal film, a low refractive index light transmitting film 244 typically made of silica aerogel, a reflection film 245, electrically conductive members 250 and 247, a thin film transistor (TFT) 246, a transparent substrate 249 typically made of glass and an insulating member 248 typically made of plastic such as polyimide and buried between the EL element and an adjacent EL element.

FIG. 14 is a schematic cross sectional view

similar to FIG. 13 but illustrating the behavior of rays of light in the electroluminescent element. In FIG. 14, the components that are same as or similar to those of FIG. 13 are denoted respectively by the same reference symbols and will not be described any further.

Referring to FIG. 14, light 251 emitted from point 261 of the EL layer 241 directly strikes the top surface 270 of the transparent substrate 249 and goes into air as refracted light 252. On the other hand, light 256 emitted also from the point 261 is totally reflected by the interface of the transparent electrode 242 and the low refractive index light transmitting film 244 to become light 257, which is then reflected by the electrically conductive metal member 250 and goes into air as light 258. Finally, light 259 emitted from the point 261 and transmitted through the inside of the EL layer 241 is reflected by the electrically conductive metal film 250 formed on the slopes and goes into air as light 260. Note that a slight gap (not shown) is formed between the electrically conductive metal film 250 and the reflection film 245 of an adjacent EL element so that they may not contact each other at the apex of the triangle formed by them.

Meanwhile, in a display apparatus according to the invention, light emitted from each EL element is amplified when the EL layer comprising a hole/electron



transport layer and the corresponding transparent electrode (anode) are sandwiched between a pair of mirrors and the light path length between the mirrors is made equal to the wavelength of light emitted from the EL layer to introduce the structure of a resonator into the EL element. Then, amplified light can be taken out by arranging a half mirror between the transparent substrate and the transparent electrode. Such an arrangement will be discussed below.

In the above described arrangement, the extent of increase G of the intensity of light emitted in a direction perpendicular to the transparent substrate depends on the reflectances of the mirrors, or the reflectance Rc of the reflection electrode (cathode) and the reflectance Rh of the half mirror and expressed by formula (1) below, which is shown in Monthly Display, October, 1998, p. 107.

$$G = (1 + (Rc)^{1/2})^2 \cdot (1 - Rh) / (1 - (Rc \cdot Rh)^{1/2})^2 \quad \dots (1)$$

If Rc is 90% and Rh is 0%, the value of G is 3.8 times greater than that of an ordinary EL element that does not have the structure of a resonator. If Rc is 90% and Rh is 85%, the value of G is 9.5 times greater than that of an EL element where Rc is 90% and Rh is 0%.

Additionally, the value of G can be raised or lowered depending on the values of Rc and Rh.

Therefore, a very bright display screen can be realized by introducing such a structure into a display device. When such a display device is placed in a light place, the viewers may feel it difficult to view the displayed image if the value of  $R_h$  is made large because both background light and room light are reflected. However, if such a display device is used in a dark place for a projector, neither background light nor room light give rise to any reflection problem.

Therefore, the luminance of the image projected on a display screen by a projector can be increased when EL elements and half mirrors are combined to increase the intensity of light emitted in a direction perpendicular to the transparent substrate and the effect of the increased intensity of light and that of the increase in the quantity of light due to the transparent members and the reflection films as obtained in a display device according to the invention are combined.

FIG. 15 is a schematic cross sectional view of an electroluminescent (EL) element having a half mirror formed on a transparent substrate and operating as a pixel in the ninth embodiment of display device according to the invention. This embodiment differs from the first embodiment only in that a half mirror 160 is arranged between the transparent electrode 120 of each EL element and the transparent substrate 150. Otherwise, this embodiment is same and identical with

the first embodiment. Therefore, in FIG. 15, the components that are same as or similar to those of FIG. 3 are denoted respectively by the same reference symbols and will not be described any further.

5 In this embodiment, the light path length between the reflector electrode 100 and the half mirror 160 is made equal to a half of the wavelength of light emitted from the EL element 300. Thus, these components form a resonator so that light can be taken out with an  
10 increased intensity. In this embodiment again, light totally reflected by the interfaces B1 and B2 is reflected by the reflection film 130 and emitted to the outside by way of the transparent substrate 150 to provide the advantage of increasing the efficiency of  
15 utilization of light as in the first embodiment.

FIG. 16 is a schematic cross sectional view of an electroluminescent (EL) element having a half mirror formed on a transparent substrate and operating as a pixel in the tenth embodiment of display device  
20 according to the invention. This embodiment differs from the fourth embodiment only in that a half mirror 160 is arranged between the transparent electrode 120 of each EL element and the transparent substrate 150. Otherwise, this embodiment is same and identical with  
25 the fourth embodiment. Therefore, in FIG. 16, the components that are same as or similar to those of FIG. 7 are denoted respectively by the same reference

symbols and will not be described any further.

In this embodiment, the light path length between the reflector electrode 100 and the half mirror 160 is made equal to a half of the wavelength of light emitted from the EL element 300. Thus, these components form a resonator so that light can be taken out with an increased intensity. In this embodiment again, light totally reflected by the interfaces B1 and B2 is reflected by the reflection film 330 and emitted to the outside by way of the transparent substrate 150 to provide the advantage of increasing the efficiency of utilization of light as in the fourth embodiment.

The ninth and tenth embodiments can suitably be used for projectors for the above described reason. FIG. 17 is a conceptual illustration of a projector realized by using a display device shown in FIG. 15 or FIG. 16. In FIG. 17, reference symbol 400 denotes a display device comprising EL elements having a configuration as shown in FIG. 15 or FIG. 16. The image of the display device 400 is projected onto a display screen 402 by way of a projection lens 401. With this arrangement, the projected image is by far brighter than the image produced by any comparable known system.

Referring to FIG. 15 and FIG. 16, the half mirror 160 typically has a four-layered structure of  $\text{TiO}_2$  layer/ $\text{SiO}_2$  layer/ $\text{TiO}_2$  layer/ $\text{SiO}_2$  layer. When the

central wavelength of light emitted from the EL element is  $\lambda$ , the light path length of each of the layers is equal to  $\lambda/4$ . In the above described arrangement, the end  $\text{SiO}_2$  layer is directly formed on the transparent substrate 150 by deposition.

Alternatively, the half mirror 160 may have a well known structure formed by repeatedly laying a pair of layers of  $\text{TiO}_2$  layer/ $\text{SiO}_2$  layer. With such an arrangement again, the end  $\text{SiO}_2$  layer is directly formed on the transparent substrate 150 by deposition.

FIG. 18 is a schematic cross sectional view of a half mirror structure having eight layers realized by arranging four pairs of  $\text{TiO}_2$  layer/ $\text{SiO}_2$  layer. In FIG. 18, the layer denoted by ITO corresponds to the transparent electrode 120 in FIG. 15 or FIG. 16 and the layer denoted by G corresponds to the transparent substrate 150 in FIG. 15 or FIG. 16. Table 1 below shows some of the details of the films of the half mirror.

Table 1

$$\lambda = 600\text{nm}$$

No.	mat.	n	d (nm)
0	G	1.46	
1	SiO <sub>2</sub>	1.485217	85
2	TiO <sub>2</sub>	2.298664	72
3	SiO <sub>2</sub>	1.485217	92
4	TiO <sub>2</sub>	2.298664	82
5	SiO <sub>2</sub>	1.485217	81
6	TiO <sub>2</sub>	2.298664	45
7	SiO <sub>2</sub>	1.485217	25
8	TiO <sub>2</sub>	2.298664	51
9	ITO	1.9	

FIG. 19 is a graph illustrating the reflectance of the above described half mirror structure of eight layers relative to light perpendicularly striking the half mirror.

FIGS. 20A through 20C are graphs illustrating the reflectance of a half mirror structure having eight layers in different aspects. FIG. 20A is a graph illustrating the reflectance of the above described half mirror structure having eight layers for S polarized light with a wavelength range between 400nm and 700nm and a range of angle of incidence within 30°. FIG. 20B is a graph illustrating the reflectance of the above described half mirror structure having eight layers for P polarized light with a wavelength range between 400nm and 700nm and a range of angle of

incidence within  $30^\circ$ . FIG. 20C is a graph illustrating the average reflectance of the above described half mirror structure having eight layers for light with a wavelength range between 400nm and 700nm and a range of angle of incidence within  $30^\circ$ , or  $\{( \text{reflectance for S polarized light} ) + ( \text{reflectance for P polarized light} )\} / 2$ .

Table 2 below shows the reflectance, the transmittance and the phases of reflected wave and transmitted wave of the above described half mirror structure having eight layers for light with an angle of incidence of  $0^\circ$ .

Table 2

theta	Reflectance					Transmittance					Phase							
	wl	rs	(s)	rp	(p)	ra	(av)	(s)	tp	(p)	ta	(av)	prp-deg	(rs)	(rp)	(ts)	ptp-deg	(tp)
0	400	53.08212	53.08212	53.08212	46.91788	46.91788	46.91788	185.682	185.682	111.147	111.147	185.682	185.682	111.147	111.147	185.682	185.682	111.147
0	410	48.17657	48.17657	48.17657	51.82343	51.82343	51.82343	189.928	189.928	142.852	142.852	189.928	189.928	142.852	142.852	189.928	189.928	142.852
0	420	39.00835	39.00835	39.00835	60.99165	60.99165	60.99165	214.67	214.67	171.521	171.521	214.67	214.67	171.521	171.521	214.67	214.67	171.521
0	430	26.21536	26.21536	26.21536	73.78464	73.78464	73.78464	227.604	227.604	199.797	199.797	227.604	227.604	199.797	199.797	227.604	227.604	199.797
0	440	14.30588	14.30588	14.30588	85.69412	85.69412	85.69412	232.298	232.298	228.568	228.568	232.298	232.298	228.568	228.568	232.298	232.298	228.568
0	450	9.693069	9.693069	9.693069	90.30693	90.30693	90.30693	220.31	220.31	256.921	256.921	220.31	220.31	256.921	256.921	220.31	220.31	256.921
0	460	13.8806	13.8806	13.8806	86.1194	86.1194	86.1194	210.327	210.327	283.124	283.124	210.327	210.327	283.124	283.124	210.327	210.327	283.124
0	470	22.45843	22.45843	22.45843	77.54157	77.54157	77.54157	215.223	215.223	306.185	306.185	215.223	215.223	306.185	306.185	215.223	215.223	306.185
0	480	31.06662	31.06662	31.06662	68.93338	68.93338	68.93338	226.654	226.654	326.221	326.221	226.654	226.654	326.221	326.221	226.654	226.654	326.221
0	490	37.91265	37.91265	37.91265	62.08735	62.08735	62.08735	240.139	240.139	343.856	343.856	240.139	240.139	343.856	343.856	240.139	240.139	343.856
0	500	42.79684	42.79684	42.79684	57.20316	57.20316	57.20316	254.308	254.308	359.734	359.734	254.308	254.308	359.734	359.734	254.308	254.308	359.734
0	510	46.04912	46.04912	46.04912	53.95088	53.95088	53.95088	268.788	268.788	14.359	14.359	268.788	268.788	14.359	14.359	268.788	268.788	14.359
0	520	48.07543	48.07543	48.07543	51.92457	51.92457	51.92457	283.493	283.493	28.083	28.083	283.493	283.493	28.083	28.083	283.493	283.493	28.083
0	530	49.23057	49.23057	49.23057	50.76943	50.76943	50.76943	298.4	298.4	41.143	41.143	298.4	298.4	41.143	41.143	298.4	298.4	41.143
0	540	49.80049	49.80049	49.80049	50.19951	50.19951	50.19951	313.475	313.475	53.686	53.686	313.475	313.475	53.686	53.686	313.475	313.475	53.686
0	550	50.00978	50.00978	50.00978	49.9022	49.9022	49.9022	328.653	328.653	65.797	65.797	328.653	328.653	65.797	65.797	328.653	328.653	65.797
0	560	50.02395	50.02395	50.02395	49.7005	49.7005	49.7005	343.833	343.833	77.517	77.517	343.833	343.833	77.517	77.517	343.833	343.833	77.517
0	570	49.98419	49.98419	49.98419	50.01581	50.01581	50.01581	358.889	358.889	88.857	88.857	358.889	358.889	88.857	88.857	358.889	358.889	88.857
0	580	49.95105	49.95105	49.95105	50.04895	50.04895	50.04895	13.685	13.685	99.813	99.813	13.685	13.685	99.813	99.813	13.685	13.685	99.813
0	590	49.96959	49.96959	49.96959	50.03041	50.03041	50.03041	28.089	28.089	110.374	110.374	28.089	28.089	110.374	110.374	28.089	28.089	110.374
0	600	50.04673	50.04673	50.04673	49.95327	49.95327	49.95327	41.992	41.992	120.53	120.53	41.992	41.992	120.53	120.53	41.992	41.992	120.53
0	610	50.16668	50.16668	50.16668	49.83332	49.83332	49.83332	55.313	55.313	130.276	130.276	55.313	55.313	130.276	130.276	55.313	55.313	130.276
0	620	50.30027	50.30027	50.30027	49.69973	49.69973	49.69973	68.003	68.003	139.615	139.615	68.003	68.003	139.615	139.615	68.003	68.003	139.615
0	630	50.41309	50.41309	50.41309	49.58691	49.58691	49.58691	80.044	80.044	148.557	148.557	80.044	80.044	148.557	148.557	80.044	80.044	148.557
0	640	50.47114	50.47114	50.47114	49.52866	49.52866	49.52866	91.442	91.442	157.12	157.12	91.442	91.442	157.12	157.12	91.442	91.442	157.12
0	650	50.44449	50.44449	50.44449	49.55551	49.55551	49.55551	102.225	102.225	165.326	165.326	102.225	102.225	165.326	165.326	102.225	102.225	165.326
0	660	50.30878	50.30878	50.30878	49.69122	49.69122	49.69122	112.43	112.43	173.199	173.199	112.43	112.43	173.199	173.199	112.43	112.43	173.199
0	670	50.04538	50.04538	50.04538	49.95462	49.95462	49.95462	122.101	122.101	180.768	180.768	122.101	122.101	180.768	180.768	122.101	122.101	180.768
0	680	49.64119	49.64119	49.64119	50.35681	50.35681	50.35681	131.287	131.287	198.059	198.059	131.287	131.287	198.059	198.059	131.287	131.287	198.059
0	690	49.0876	49.0876	49.0876	50.9124	50.9124	50.9124	140.035	140.035	201.911	201.911	140.035	140.035	201.911	201.911	140.035	140.035	201.911
0	700	48.37985	48.37985	48.37985	51.62015	51.62015	51.62015	148.392	148.392	201.911	201.911	148.392	148.392	201.911	201.911	148.392	148.392	201.911



Table 3 below shows the reflectance of the above described half mirror structure having eight layers for S polarized light with a wavelength range between 400nm and 700nm and a range of angle of incidence within 30°.

Table 3

theta	0	5	10	15	20	25	30
wl	rs(0°)	rs(5°)	rs(10°)	rs(15°)	rs(20°)	rs(25°)	rs(30°)
400	53.08212	53.3949	54.12334	54.48678	52.68927	45.05927	28.26013
410	48.17657	48.0306	47.21124	44.43833	37.23653	24.06525	26.01796
420	39.00835	38.22824	35.44011	29.42095	19.95582	18.17546	45.26679
430	26.21536	24.98771	21.19834	15.57016	14.30957	31.02331	59.49687
440	14.30588	13.43388	11.59921	12.37497	23.11551	45.36075	67.03681
450	9.693069	10.04325	12.33233	20.02936	35.63604	54.95319	70.74039
460	13.8806	15.35109	20.54906	30.85611	45.51777	60.55814	72.33646
470	22.45843	24.35017	30.22547	39.9916	52.03934	63.59624	72.73219
480	31.06662	32.88383	38.22425	46.44271	56.006	65.04069	72.45333
490	37.91265	39.47661	43.95743	50.6249	58.23293	65.50564	71.85011
500	42.79684	44.09124	47.75917	53.15198	59.31593	65.40039	71.17301
510	46.04912	47.11221	50.11556	54.53563	59.6761	65.01588	70.5896
520	48.07543	48.95622	51.45082	55.16329	59.61919	64.56017	70.18505
530	49.23057	49.97527	52.0999	55.32672	59.36993	64.16882	69.97028
540	49.80049	50.44935	52.32197	55.24517	59.08617	63.90939	69.90289
550	50.00978	50.59664	52.3144	55.07728	58.86468	63.79144	69.91378
560	50.02995	50.58197	52.22066	54.92683	58.74761	63.78334	69.92978
570	49.98419	50.5215	52.13468	54.84791	58.73335	63.8316	69.88688
580	49.95105	50.48664	52.10589	54.8533	58.79092	63.8771	69.73522
590	49.96959	50.50974	52.14688	54.92587	58.87459	63.86576	69.43801
600	50.04673	50.59212	52.24333	55.03077	58.93546	63.75335	68.97219
610	50.16668	50.71388	52.36478	55.12621	58.92895	63.50638	68.31834
620	50.30027	50.84343	52.47397	55.17116	58.81831	63.10088	67.46499
630	50.41309	50.94525	52.53369	55.12983	58.5754	62.52028	66.40318
640	50.47114	50.98534	52.51087	54.97339	58.17983	61.75344	65.12588
650	50.44449	50.93435	52.37858	54.6802	57.61763	60.79313	63.62755
660	50.30878	50.76881	52.11629	54.23494	56.8798	59.63484	61.90393
670	50.04538	50.47107	51.70927	53.62746	55.96098	58.2761	59.95224
680	49.64119	50.0289	51.14787	52.85181	54.85879	56.7164	57.77195
690	49.0876	49.43447	50.4264	51.90519	53.57301	54.95695	55.36522
700	48.37985	48.68366	49.54245	50.78745	52.1055	53.00111	52.73804

00003572-11370



Table 5 below shows the average reflectance of the above described half mirror structure having eight layers for light with a wavelength range between 400nm and 700nm and a range of angle of incidence within 30°, or  $\{(\text{reflectance for S polarized light}) + (\text{reflectance for P polarized light})\} / 2$ .

Table 5

theta	0	5	10	15	20	25	30
wl	ra(0°)	ra(5°)	ra(10°)	ra(15°)	ra(20°)	ra(25°)	ra(30°)
400	53.08212	52.90377	52.11843	49.84207	44.30421	33.21989	17.9874
410	48.17657	47.5384	45.2314	40.05782	30.38105	17.26997	16.056
420	39.00835	37.77521	33.71342	26.09809	16.01261	12.6568	27.7809
430	26.21536	24.64979	20.04822	13.70689	11.20038	21.12412	37.56531
440	14.30588	13.24112	10.93139	10.67737	17.66133	31.65583	43.38432
450	9.693069	9.874841	11.47822	17.05717	27.69186	39.45311	46.45974
460	13.8806	15.06241	19.0995	26.58057	36.20309	44.3854	47.82233
470	22.45843	23.92146	28.28045	34.96535	42.15589	47.21139	48.16788
480	31.06662	32.36507	36.00905	41.08771	45.93428	48.62288	47.97648
490	37.91265	38.91422	41.62603	45.15622	48.12948	49.1419	47.58346
500	42.79684	43.51183	45.38926	47.66336	49.24671	49.15505	47.20951
510	46.04912	46.52845	47.74164	49.06681	49.67771	48.94506	46.97491
520	48.07543	48.37368	49.08793	49.73411	49.72024	48.70591	46.91465
530	49.23057	49.39653	49.75572	49.95092	49.5942	48.55107	47.00091
540	49.80049	49.87589	50.00175	49.93394	49.44944	48.52372	47.16988
550	50.00978	50.02954	50.02233	49.83873	49.37168	48.61311	47.34652
560	50.02995	50.02208	49.95967	49.76445	49.39162	48.77482	47.46174
570	49.98419	49.96933	49.90597	49.75997	49.49842	48.94995	47.46103
580	49.95105	49.94226	49.90863	49.83334	49.65527	49.07957	47.30635
590	49.96959	49.97277	49.97843	49.96402	49.81396	49.1132	46.97448
600	50.04673	50.0618	50.09971	50.11525	49.92568	49.01204	46.45381
610	50.16668	50.18918	50.24123	50.24471	49.94756	48.74909	45.74126
620	50.30027	50.32318	50.36545	50.31175	49.84555	48.30748	44.8396
630	50.41309	50.42827	50.43529	50.28161	49.59476	47.67836	43.75552
640	50.47114	50.47048	50.41805	50.12682	49.17843	46.85894	42.49826
650	50.44449	50.42056	50.2873	49.82738	48.58661	45.85097	41.07873
660	50.30878	50.25518	50.02316	49.36976	47.81466	44.65958	39.50894
670	50.04538	49.95682	49.61159	48.74578	46.86198	43.29243	37.80165
680	49.64119	49.51344	49.04371	47.95167	45.73135	41.75951	35.97038
690	49.08776	48.91739	48.31467	46.98698	44.42803	40.07255	34.0292
700	48.37985	48.16473	47.42298	45.8541	42.95967	38.24515	31.99305

As shown above, the reflectance of the above described half mirror having eight layers is substantially constant and about 50% for visible light with a range of angle of incidence within  $30^\circ$ .

5 According to the formula (1) described earlier, the increase G in the intensity of light is about 17 times greater than that of an ordinary element having no resonator structure when Rc is 90% and Rh is 50%.  
Therefore, the quantity of light at the image forming  
10 surface is increased by 17 times when a display device comprising half mirrors is used for a projector and  $NA = \sin 30^\circ$ , or the lens is used with a full aperture of F number = 1.

Note that the light path length between the half  
15 mirror 160 having four or eight layers and the reflector electrode 100 is made equal to  $1/2$  of the wavelength of light emitted from the EL element in the embodiments of FIGS. 15 and 16. However, it may alternatively be made equal to integer times of  $1/2$  of  
20 the wavelength of emitted light.

Besides, since the cathode, or the reflector electrode 100, is made of metal such as aluminum (Al), it reflects not only light from the EL layer 110 also external light directed to the viewer. However, as  
25 external light is reflected, the contrast of the image displayed on the display screen of the display device is reduced. In other words, the reflection of external

light needs to be eliminated or minimized. Japanese Patent Application Laid-Open No. 8-8065 discloses an arrangement for reducing external light by making the cathode have two-layered structure, realizing the EL layer 110 as a light absorbing layer and arranging another electrode layer typically made of aluminum (Al).

FIG. 21 is a schematic cross sectional view of an electroluminescent (EL) element having a light absorbing layer formed on a transparent substrate and operating as a pixel in the eleventh embodiment of display device according to the invention. This embodiment differs from the above described ninth embodiment only in that a light absorbing layer 100a is formed between the EL layer 110 and the reflector electrode 100 of each EL element 300. Otherwise, this embodiment is identical with the ninth embodiment. Therefore, in FIG. 21, the components that are same as or similar to those of FIG. 15 are denoted respectively by the same reference symbols and will not be described any further.

In this embodiment, total reflection is realized at the interface of the light absorbing layer 100a and the EL layer 110 by making the refractive index of the light absorbing layer 100a located at a side of the EL layer lower than that of the EL layer 110. With this arrangement, light is totally reflected to return into

the EL layer and reflected again by the reflection film 130 to consequently increase the proportion of light emitted to the outside from the display device.

When the EL layer 110 is made of aluminum quinolinol (alq), its refractive index will be about 1.73. Therefore, then, the light absorbing layer 100a is preferably made of MgO having a refractive index of 1.70. If the EL layer 110 comprises an electron transport layer, the refractive index of the light absorbing layer 100a needs to be made lower than that of the electron transport layer.

Referring to FIG. 21, light 1003 emitted from the EL layer 110 is totally reflected by the interface of the light absorbing layer 100a and the EL layer 110 to become light 1004, which is then reflected by the reflection film 130 to become light 1005 and go out of the display device.

FIG. 22 is a schematic cross sectional view of an electroluminescent (EL) element having a light absorbing layer in the twelfth embodiment of display device according to the invention. This embodiment differs from the above described tenth embodiment only in that a light absorbing layer 100a is formed between the EL layer 110 and the reflector electrode 100 of each EL element 300. Otherwise, this embodiment is identical with the tenth embodiment. Therefore, in FIG. 22, the components that are same as or similar to

those of FIG. 16 are denoted respectively by the same reference symbols and will not be described any further.

5 The light absorbing layer 100a of this embodiment is preferably made of a material same as its counterpart of the eleventh embodiment. Referring to FIG. 22, light 1003 emitted from the EL layer 110 is totally reflected by the interface of the light absorbing layer 100a and the EL layer 110 to become  
10 light 1004, which is then reflected by the reflection film 330 to become light 1005 and go out of the display device.

As described above in detail, according to the invention, it is no longer necessary to arrange a  
15 protection film for shielding each EL element from ambient air after forming the transparent members. Nor is it necessary to design the manufacturing steps in such a way that, when a reflection film is formed on each transparent member, it is arranged so as not to  
20 contact the transparent electrode and the reflector electrode that sandwich the reflection film. Thus, it is possible to simplify the manufacturing steps and reduce the manufacturing cost. Therefore, according to the invention, the transparent members protect the EL  
25 elements from ambient air and light emitted from the EL layer of each EL element can be efficiently taken out to the outside by the reflection film formed on the

corresponding transparent member.

The present invention is by no means limited to  
the above described embodiments, which may be modified  
or altered in various different ways without departing  
5 from the spirit or scope of the general inventive  
concept as defined by the appended claims and their  
equivalents.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222